# APPLICATION UNDER UNITED STATES PATENT LAWS

		•	• •
Atty. Dkt. No.	PW 281475 (M#)		
nvention:	INTRINSICALLY GEL-FREE, RANDOMLY	BRANCH	IED POLYAMIDE
nventor (s):	Atze Jan NIJENHUIS Rene ABERSON Boudewijn Jan Robert SCHOLTENS		
	•		Pillsbury Winthrop LLP Intellectual Property Group 1600 Tysons Boulevard
			McLean, VA 22102
			Attorneys Telephone: (703) 905-2000
Anni Vani Vani Inni Inni Inni Vani Vani Vani			•
- FE			This is a:
		_	
			Provisional Application
			Regular Utility Application
		$\boxtimes$	Continuing Application  ☑ The contents of the parent are incorporated by reference
:			PCT National Phase Application
			Design Application
			Reissue Application
			Plant Application
	·		Substitute Specification Sub. Spec Filed
			in App. No/
			Marked up Specification re Sub. Spec. filed

## **SPECIFICATION**

In App. No

25

30

35

5 INTRINSICALLY GEL-FREE, RANDOMLY BRANCHED POLYAMIDE

The invention relates to a randomly branched polyamide comprising at least units derived from:

- 10 1. AB monomers,
  - 2. at least one compound I, being a carboxylic acid  $(A_v)$  having a functionality  $v \ge 2$  or an amine  $(B_w)$  having a functionality  $w \ge 2$ ,
- 3. at least one compound II, being a carboxylic acid (A<sub>v</sub>) having a functionality v ≥ 3 or an amine (B<sub>w</sub>) having a functionality w ≥ 3, compound II being a carboxylic acid if compound I is an amine or compound II being an amine if compound I is a carboxylic acid.

In the context of this application, with the term "randomly branched" is meant that the branching points are randomly distributed in the polyamide chain.

Such a randomly branched polyamide is known from EP-345.648-Bl. However, a problem encountered with the randomly branched polyamide according to EP-345.648-Bl is that the randomly branched polyamide is not intrinsically gel-free so that, while the randomly branched polyamide can for instance be obtained as a gel-free melt, during further processing of the randomly branched polyamide, gel formation may as yet occur. In the context of this application gel formation is understood to be a process involving the formation of a network in a polymer material. Gel formation gives rise to, among other things, the formation of visible inhomogeneities ("gels") during processing of the

25

30

10

randomly branched polyamide into, for instance, films or fibres and to deterioration of the mechanical properties of polyamide objects obtained from the randomly branched polyamide. It is also known that when randomly branched polyamide is processed in equipment where local overheating may take place or where polyamide material may accumulate, for instance in extruders and mixers, it may contain strongly crosslinked polyamide.

It is desirable to have intrinsically gelfree randomly branched polyamide available. In the
context of this application "intrinsically gel-free" is
understood to mean that the composition of the randomly
branched polyamide is such that it cannot form
crosslinked polyamide (and therefore no gels), in
particular during the prepolymerization, the
polymerization, the post-condensation, the processing,
for instance into films or fibres, and the storage of
the randomly branched polyamide, and this at a variety
of ambient factors, for instance at elevated
temperature and pressure.

Although the prevention of gel formation in polymeric materials has been receiving a great deal of attention in practice, at this point of time neither a structural nor a systematic approach is known to provide an adequate solution to the problem of obtaining intrinsically gel-free, randomly branched polyamide from AB monomers.

It is the aim of the inventors to provide such an intrinsically gel-free, randomly branched polyamide comprising at least units derived from:

- 1. AB monomers,
- 2. at least one compound I, being a carboxylic acid  $(A_r)$

having a functionality  $v \ge 2$  or an amine  $(B_w)$  having a functionality  $w \ge 2$ ,

3. at least one compound II, being a carboxylic acid (A<sub>v</sub>) having a functionality v ≥ 3 or an amine (B<sub>w</sub>) having a functionality w ≥ 3, compound II being a carboxylic acid if compound I is an amine or compound II being an amine if compound I is a carboxylic acid.

This aim is achieved when the amounts of all units derived from carboxylic acids and amines in the polyamide satisfy formula 1

$$P < 1 / [(F_A - 1).(F_B - 1)]$$
 (1)

15 where:

5

$$P = \{ \Sigma (n_i, f_i) \}_x / [\Sigma (n_i, f_i) \}_y$$
 (2)

where  $P \le 1$  and either X = A and Y = B, or X = B and Y = A, and

$$F_{x} = \Sigma (n_{i}.f_{i}^{2}) / \Sigma(n_{i}.f_{i})$$
 (3)

for, respectively, all carboxylic acids (X = A) and all amines (X = B), where  $f_i$  is the functionality of either the carboxylic acid  $(f_i = v_i)$  or amine  $(f_i = w_i)$ ,  $n_i$  being the number of moles of the carboxylic acid or amine and the summation involving all units derived from carboxylic acids and amines in the polyamide.

In the context of the present invention AB monomer is understood to be a monomer that has both a carboxylic acid group (A) and an amine group (B).

In the context of the present application

20

25

leastes celent

5

10

15

20

25

30

compound I and compound II are also understood to be mixtures of several carboxylic acids having the same functionality or mixtures of several amines having the same functionality.

In the context of the present application carboxylic acid and amine are understood to be, respectively, a compound which, besides one or more carboxylic acid groups, does not carry any amine groups and the other way round. It therefore follows that units derived from carboxylic acids or amines in the polymer have a chemical composition that differs from that of the units derived from the AB monomers. Carboxylic acid group is in the context of the present application understood to be a group that can form a covalent bond with an amine group, for instance -COOH, -COHal (Hal = halogen), -CO<sub>2</sub>R in which R is an alkyl residue with 1 to 20 carbon atoms and -SO<sub>2</sub>Hal (Hal = halogen).

In the context of the present application functionality is understood to be the number of functional groups in the carboxylic acid or the amine that can form a bond with other carboxylic acids, amines or AB monomers to form the randomly branched polyamide according to the invention. A functional group that cannot form this bond, for instance a sterically hindered amine group or an aromatic amine group, is not considered as a functional group in determining the functionality. Likewise, the functionality is equated to 1 if two functional groups at a compound are both involved in a single bond with a third functional group, for instance two COOH groups that are close together which form an imide bond with an amine, for instance in the compound orthodicarboxybenzene.

15

20

25

30

Preferably, the functionality v or w of compound I can be chosen from 2, 3, 4, 5 and 6. More preferably, the functionality of compound I is 2. Preferably, the functionality v or w of compound II can be chosen from 3, 4, 5 and 6. More preferably, the functionality of compound II is 3.

Eligible AB monomers are all AB monomers that can be used for the production of polyamides, in particular  $\alpha, \omega$ -amino acids and/or lactams, for instance caprolactam, laurine lactam and dodecalactam, as well as the corresponding amino acids and aromatic amino acids, for instance p-(aminomethyl)-benzoic acid. Preferably, the lactam is  $\epsilon$ -caprolactam.

Eligible carboxylic acids (A<sub>v</sub>) are preferably difunctional carboxylic acids, for instance adipic acid, dodecane dicarboxylic acid, isophthalic acid and terephthalic acid and trifunctional carboxylic acids, for instance 1,3,5-tris(caproic acid)melamine, trimesic acid and trimeric fatty acids with 50-60 carbon atoms as well as esters and anhydrides of said carboxylic acids. Preferably, the difunctional carboxylic acid is terephthalic acid. Preferably, the trifunctional carboxylic acid is 1,3,5-tris(caproic acid)melamine (TCAM) or trimesic acid.

Eligible amines (B<sub>w</sub>) are preferably difunctional amines, for instance diaminobutane, diaminohexane, diaminododecane, cyclic amines, for instance 1,4-diaminocyclohexane, 4,4'-diaminobicyclohexylamine, 1,3- and 1,4-xylylene diamine and trifunctional amines, for instance trisaminononane and bis (hexamethylene triamine). Preferably, the difunctional amine is 1,6-hexamethylene diamine. Preferably, the trifunctional amine is

(0

15

20

bis (hexamethylene triamine).

Besides the units derived from compounds I and II according to the invention also other units derived from carboxylic acids and amines may be present, for instance monofunctional carboxylic acids and amines (chain terminators).

Although the aim of the invention according to EP-345.648-Bl is not the aim of the present invention, while said publication does not mention the measures according to the present invention, either, it does mention, besides a number of randomly branched polyamides that do not satisfy the measures according to the present invention, also a number of randomly branched polyamides which coincidentally satisfy the measures according to the invention. These randomly branched polyamides are excluded from the application, more specifically the randomly branched polyamides that are built up of units derived from carboxylic acids (A<sub>v</sub>) having a functionality v and amines (B<sub>w</sub>) having a functionality w, in the following amounts (in µmol/g of polyamide):

The intrinsically gel-free, randomly

branched polyamide according to the invention can be produced using methods known to one skilled in the art, both via a batch process and via a continuous process. According to a first embodiment all AB monomers,

<sup>-</sup>  $B_1$  (20),  $B_3$  (60) and  $A_2$  (20)

<sup>-</sup>  $B_1$  (10),  $B_3$  (60) and  $A_2$  (30)

<sup>25 -</sup>  $B_1$  (120),  $B_2$  (30) and  $A_3$  (60)

<sup>-</sup>  $B_1$  (150),  $B_2$  (30) and  $A_3$  (70)

<sup>-</sup>  $B_1$  (170),  $B_3$  (30),  $A_2$  (60) and  $A_3$  (60)

20

25

process.

5

10

carboxylic acids and amines are polymerized in amounts, according to the invention in a reactor at a suitable temperature and pressure. According to a second embodiment the carboxylic acids and amines are added to a melt of a polyamide comprising units derived from AB monomers.

The gel-free, randomly branched polyamide according to the invention can also contain the customary additives, for instance flame retardants, fillers, release agents, lubricants and colourants.

The intrinsically gel-free, randomly branched polyamide according to the invention is eminently suitable for the production of fibre, film, foams and moulded articles. In particular, the intrinsically gel-free, randomly branched polyamide according to the invention is eminently suitable for the production of thin film, in particular flat film. The inventors have established that no gels could be observed in said thin film obtained with the polyamide according to the invention. Another surprising advantage of the polyamide according to the invention is that no or hardly any neck-in occurs in the production of flat film. Neck-in is the decrease in the ratio of film width to die width during the film forming process. This surprising advantage allows films to be formed in a simple manner without the known attendant measures to prevent neck-in, for instance cooling of the film edges during the film forming

The invention therefore also relates to a process for the production of film obtained from the polyamide according to the invention, as well as to the film obtained with the polyamide according to the invention.



The invention will now be elucidated on the basis of examples, without however being limited thereto.

PH

25

5

10

Examples

- A Built Description of The Drawings -
Examples I-VIII: Graphical development of the gel-free

concentration range

For a number of combinations of carboxylic

acids and amines (Table 1), formulas (1)-(3) were developed into a graphical representation for a combination of three carboxylic acids or amines (Figures 1-8), without however limiting the invention to the examples given. In the figures it was shown what amounts (expressed as mole fractions) of units derived from carboxylic acids and amines an intrinsically gelfree, randomly branched polyamide can contain. concentration range indicated by small circles the randomly branched polyamide is non-intrinsically gelfree. It is remarkable to note that the intrinsically gel-free nature of a randomly branched polyamide does not depend on the absolute amount of units derived from a carboxylic acid or amine, but only on the relative ratio of the units derived from the carboxylic acids and amines. This also means that the intrinsically gelfree nature of a randomly branched polyamide according to the invention does not depend on the amount of units derived from AB monomers. A third remarkable fact is that in the polyamide according to the invention all units derived from carboxylic acids can be-replaced by amines, and the other way round, without this changing the gel-free nature of a polyamide. For instance, the concentration range for the units derived from carboxylic acids A<sub>1</sub> and A<sub>3</sub> and the amine B<sub>2</sub> is the same

as that for units derived from amines  $B_1$  and  $B_3$  and the carboxylic acid  $A_2$  (Figure 1).

Table 1: Combinations of carboxylic acids and amines

Example	Carboxylic acids	Amines	Figure
I	$A_1$ , $A_3$	B <sub>2</sub>	1
II ,	A <sub>1</sub> , A <sub>3</sub>	В3	2
III	A <sub>1</sub> , A <sub>4</sub>	B <sub>2</sub>	3
IV	A <sub>1</sub> , A <sub>4</sub>	B <sub>3</sub>	4
v	A <sub>1</sub> , A <sub>5</sub>	B <sub>2</sub>	5
VI	$A_1$ , $A_5$	B <sub>3</sub>	6
VII	$A_1$ , $A_6$	B <sub>2</sub>	7
VIII	$A_1$ , $A_6$	B <sub>3</sub>	8

Preparation of gel-free, randomly branched polyamides

#### Process 1

aminocaproic acid, 2 g of water and varying amounts of carboxylic acids and amines (see Table 2 for the molar ratios) were mixed in a glass tube at 90°C. The tube was equipped with a reflux cooler and was purged three times with vacuum/nitrogen before use, following which the reaction mixture was heated to 260-270°C in a nitrogen atmosphere and was subsequently kept at this temperature for 11 hours. After cooling, the tube was broken and its contents ground and washed three times in boiling water so as to remove any unreacted caprolactam and low-molecular oligomers and subsequently dried for 24 hours in a vacuum at 80°C. The polymer obtained was white. The washed and dried

5

polymers were subjected to a number of analyses such as melt viscosity and intrinsic viscosity. The melt viscosity was determined using a Rheometrix 800 plate/plate apparatus as so-called zero viscosity at 230°C, in other words the dynamic melt viscosity at zero shear force. The intrinsic viscosity was determined by means of a three-point measurement (3, 4 and 5 g/l) in 85% formic acid at 25°C. All polymers in Table 1 were prepared in this way.

10

15

20

#### Process 2

In a 5-litre reactor 3.5 kg of s-caprolactam, 35 g of s-aminocaproic acid, 70 g of water and the varying amounts of additives were combined. The temperature of the reaction mixture was kept at 90°C for 5 hours, after which the mixture was heated to 275°C in about 2 hours and was kept at that temperature for 5 hours. Subsequently, the temperature was lowered to 240°C in 60 minutes and kept at that value for 3.5 hours. Next, the reactor contents were drained in a nitrogen atmosphere at 1 bar overpressure. The polymer thread flowing out the reactor was cooled in ice water and chopped into granules, which were washed with water at 100°C and subsequently dried.

25

#### Post-condensation:

The polymer obtained by means of processes 1 and 2 was post-condensed for 10 hours at 190°C in a vacuum and with a nitrogen leak.

30

#### Examples IX-XXXII

Process 1 was used to prepare a number of polyamides, the compositions being given in Table 2. In

none of the polyamides was crosslinking observed during or after the polymerization.

Table 2: Intrinsically gel-free polyamide compositions (amounts in moles).

Ex.	<b>A</b> <sub>1</sub>	Bı	A <sub>2</sub>	B <sub>2</sub>	<b>A</b> <sub>3</sub>	B <sub>3</sub>	AB monomer
IX	1	-	-	0.25	0.25	-	300
х	1	-	_	0.5	0.5	-	300
ХI	1	~	-	0.75	0.75	-	300
XII	1		-	1	1	-	300
XIII	ı	-	-	2	2	-	300
XIV	-	1	0.25	-	-	0.25	300
xv	-	ı	0.5	-	-	0.5	300
XVI	-	1	1	-	-	ì	300
XVII	-	1	2	-	-	2	300
XVIII	1	1.25	-	0.25	0.25	-	300
XIX	1	1.5	-	0.5	0.5	-	300
xx	1	2	-	ī	ī	-	300
XXI	1	3	· ~	2	2	-	300
XXII	1	1.5	-	0.5	0.5	_	300 /
XXIII	0.5	-	-	-	0.5	-	300
VXIV	0.33	-	-	0.67	1.33	-	300
xxv	0.5	-	-	0.5	ı	_	300
XXVI	0.6	-	-	0.4	0.8	-	300
XXVII	0.67	-	-	0.33	0.67	-	300
XXVII	2	-	-	2	ב	-	300
I							
XXIX	0.67	-	-	0.67	1	-	300
xxx -	0.5	-	-	0.5	1	-	300
xxxı	0.57	-	-	0.29	0.57	-	300
XXXII	1.33	-	-	1.67	1.33	_	300

#### Explanation of the abbreviations :

A<sub>1</sub> : benzoic acid

B<sub>1</sub>: hexylamine

5 A<sub>2</sub>: adipic acid

B<sub>2</sub>: hexamethylene diamine

A<sub>3</sub>: 1,3,5-tris(caproic acid) melamine

B<sub>3</sub>: bis (hexamethylene) triamine

AB monomer : s-caprolactam

10

15

#### Comparative examples A-G according to EP-B1-345.638

Process 1 was used to prepare a number of polyamides, their compositions being given in Table 3. In all polyamides crosslinking was observed during or after the polymerization.



Table 3 : Comparative examples according to EP-B1-345.638.

Comparative Exa	Example	AB monomer	В	В	A2	A <sub>3</sub>	gel for-
example	acc. to BP-		(L-252)	(N-TBA)	(ADS)	(TMS)	mation
	B1-345.638						
	(Table 2)						
A	10	aminolaurine acid 180	180	30	1	06	yes
В	11	aminolaurine acid 190	190	30	1	92	yes
ย	13	aminolaurine acid	176	28	46	56	yes
٥	15	caprolactam	210	30	ı	100	yes
B	91	caprolactam	210	30		100	yes
נצג	11	caprolactam	176	28	46	56	yes
9	18	caprolactam	124	20	32	40	yes

### Explanation of the abbreviations:

L-252

: 3-amino-1-cyclohexyl-aminopropane

N-TEA

: nitrilotriethane amine

ADS

: adipic acid

5 TMS

: trimesic acid

Mechanical properties of the polyamide according to the invention

Surprisingly, it was also found that the polyamide according to the invention combines a high melt strength with a high melt drawing degree compared to non-branched polyamide. This is shown in Figure 9.